



HighEnd Foto/Bildbearbeitung/Softproof/Vorstufe

Präsentation

ProfiFoto/Design/Softproof

Foto/Softproof/Layout allgemein

OnPress Softproof

Modell	IP300 ex	IP270 ex	IP264 ex	IP240 exLED	IP244 ex	IP220 ex	IP420 ex	IP242 LE	IP220 LE	IP213	IP201	IP190	PV700-21	PV700-42
Größe	30"	27"	26"	24"	24"	22"	42"	24"	22"	21.3"	20.1"	19"	21.3"	42"
Auflösung	2.560x1.600	2.560x1.440	1.920x1.200	1.920x1.200	1.920x1.200	1.680x1.050	1.920x1.080	1.920x1.200	1.680x1.050	1.600x1.200	1.600x1.200	1.280x1.024	1.600x1.200	1.920x1.080
Paneltyp	P-IPS	P-IPS	S-IPS	S-IPS	S-IPS	E-IPS	S-MVA	S-PVA	S-PVA	S-IPS	S-IPS	S-IPS	IPS-Pro	S-IPS
Flächenabgleich	aktiv	aktiv	5x5	7x5 plus LED	5x5	5x5	5x5	3x3	3x3	---	---	---	passiv	5x5
Helligkeit (typ.)	400 cd/m ²	400 cd/m ²	400 cd/ m ²	250 cd/ m ²	400 cd/ m ²	300 cd/ m ²	400cd/ m ²	400cd/ m ²	300 cd/ m ²	250 cd/ m ²	300 cd/ m ²	270 cd/ m ²	700 cd/ m ²	700 cd/ m ²
Kontrast (typ.)	1000:1	1000:1	1000:1	1000:1	1000:1	1000:1	1000:1	1000:1	1000:1	550:1	800:1	700:1	1000:1	1000:1
Blickwinkel (typ)	178°H/V	178°H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V	178° H/V
Gamut (NTSC CIE31)	ca. 102%	ca. 102%	ca. 92%	ca. 110%	ca. 102%	ca. 92%	ca. 92%	ca. 92%	ca. 92%	ca. 72%	ca. 72%	ca. 72%	ca. 72%	ca. 72%
Gamut (ISOcoatedv2)	max. 100%	max. 100%	max. 100%	max. 100%	max.100%	max. 100%	max. 100%	max. 100%	max. 100%	max. 93%	max. 93%	max. 93%	max. 93%	max. 93%
Gamut (Adobe-RGB)	max. 100%	max. 100%	max. 100%	max. 100%	max.100%	max. 96%	max. 96%	max. 93%	max. 93%	max. 78%	max. 78%	max. 78%	max. 93%	max. 78%
Farbtiefe	30 bit	30 bit nativ	30 bit	30 bit nativ	30 bit nativ	30 bit	30 bit nativ	30 bit	30 bit	30 bit	30 bit	30 bit	30 bit	30 bit nativ
Kalibration	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Hardware
Kalibrationsart	USB	USB	USB	USB	USB	USB	USB	USB&DDC/ci	USB &DDC/ci	USB	USB	USB	USB	USB
Präzision	48 bit	48 bit	48 bit	48 bit	48 bit	42 bit	30 bit nativ	36 bit	36 bit	30 bit	30 bit	30 bit	36 bit	36 bit
USB-Hub/Ports	USB 2.0/3	USB 2.0/3	USB2.0/2	USB2.0/2	USB2.0/2	USB2.0/2	USB2.0/2	USB2.0/2	USB2.0/2	USB1.1/2	---	---	USB2.0/2	USB2.0/2
Garantie *	60 Monate	60 Monate	60 Monate	60 Monate	60 Monate	60 Monate	36 Monate	36 Monate	36Monate	60 Monate	60 Monate	60 Monate	36 Monate	36 Monate
Pixelfehler	● ————— max.2-kein Pixelfehler im Zentrum ————— ●						ISO123406-2	● ————— max.3 ————— ●		● ————— max.2-kein Pixelfehler im Zentrum ————— ●			ISO 123406-2	ISO 123406-2
Erweiterter Modus	ja	ja	ja	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja	ja
Referenz Modus	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja	ja
UDACT	ja	ja	ja	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja	ja
SiteLizenz	ja	ja	ja	ja	ja	ja	ja	nein	nein	ja	ja	ja	ja	ja
Lichtschutzblende	ja	ja	ja	ja	ja	ja	nein	ja	ja	ja	ja	ja	ja	nein